

CISCO AIRONET 1130AG ACCESS POINT

Simple Wifi without encryption.

1. In the „SECURITY” – „SID Manager” sheet set up SSID,e.g. in my case „WPA”.
Check both interfaces and confirm your configuration by clicking „Apply”.

Security: Global SSID Manager

SSID Properties

Current SSID List

< NEW >
wpa

Delete

SSID: wpa

VLAN: < NONE > Define VLANs

Interface: Radio0-802.11G
 Radio1-802.11A

Network ID: (0,4096)

2. On the bottom of this sheet set up broadcast for SSID-a.(Set Single Guest Mode SSID)(of course if you wish).

Guest Mode/Infrastructure SSID Settings

Radio0-802.11G:

Set Beacon Mode: Single BSSID Set Single Guest Mode SSID: wpa
 Multiple BSSID

Set Infrastructure SSID: < NONE > Force Infrastructure Devices to associate only to this SSID

Radio1-802.11A:

Set Beacon Mode: Single BSSID Set Single Guest Mode SSID: wpa
 Multiple BSSID

Set Infrastructure SSID: < NONE > Force Infrastructure Devices to associate only to this SSID

Apply Cancel

3. Confirm yourself if in the „Encryption Manager” sheet - „Encryption Modes” is set up to „None”.

dzbanek